



Plasma cutting application

Commercial ship repair

Examples of plasma uses

Hull repair

Welds securing damaged or corroded hull plates, typically 8 to 12 mm (5/16 to 1/2") thick, are gouged out or cut away for the installation of new sheets.

Systems: Powermax45 or 65

Deck repair

Welds securing corroded or damaged steel decking, typically 3 to 6 mm (1/8 to 1/4") thick, are gouged out or cut away for the installation of new sheets.

Systems: Powermax45 or 65

Frame repair

Corroded or damaged steel beams, typically 6 to 10 mm (1/4 to 3/8") thick, are cut away for placement of new beams.

Systems: Powermax45 or 65

Vent and piping installation

Vent, pipe and access holes are cut into 3 to 6 mm (1/8 to 1/4") thick plates using templates.

Systems: Powermax45 or 65

Tank repair

Deteriorated sections in tanks, typically 1.6 to 3 mm (1/16 to 1/8") thick, are cut away for the placement of new panels.

Systems: Powermax30 XP

Key advantages of Powermax® systems

- Superior speed of plasma cutting results in shorter cut times and greater productivity over processes such as oxyfuel or saws.
- Easy to set up and operate.
- Piercing capability makes starting interior cuts easy.
- High cut quality reduces or eliminates secondary operations, such as grinding.
- Drag-cutting technology makes it easy to follow a line or template.
- Gouging process efficiently removes existing welds with reduced noise and smoke over conventional methods.
- System portability offers ease of use at various locations.
- Controlled arc and high cutting speeds reduce heat-affected zone and warping.
- Cut a variety of ferrous and non-ferrous metals including mild steel, stainless and aluminum – painted or rusted.
- Pilot arc control feature enables uninterrupted cutting on expanded metal.
- Machine torches are available for use on pipe beveling and cutting machines.

Hypertherm and Powermax are trademarks of Hypertherm Inc. and may be registered in the United States and/or other countries. All other trademarks are the properties of their respective owners.

© 3/2015 Hypertherm Inc. Revision 7
890220

