



Plasma cutting application

Highway equipment maintenance

Examples of plasma uses

Dump truck bed repair

Welds securing worn or damaged bed plates, typically 10 to 12 mm (3/8 to 1/2") thick, are gouged out or the plates are cut away for installation of new plates.

Systems: Powermax45® XP, Powermax65 SYNC™, or 85 SYNC

Loader shovel repair

Welds securing wear plates, typically 3 to 12 mm (1/8 to 1/2") thick, and damaged shovel teeth are gouged out to allow the installation of new parts.

Systems: Powermax45 XP, Powermax65 SYNC, or 85 SYNC

Bulldozer track repair

Corroded steel bolts are cut off to remove the damaged shoes for the installation of new track.

Systems: Powermax30 XP, 45 XP, Powermax65 SYNC, or 85 SYNC

Plow repair

Welds securing wear plates, typically 12 to 20 mm (1/2 to 3/4") thick, and plow blades are gouged out for the installation new parts.

Systems: Powermax65 SYNC, 85 SYNC, or 105 SYNC

Truck maintenance

Corroded or collision damaged body panels, typically 3 mm (1/8") thick, are cut away for the installation of replacement panels.

Systems: Powermax30 XP, 45 XP, or Powermax65 SYNC

Key advantages of Powermax systems

- Superior speed of plasma cutting results in shorter cut times and greater productivity over processes such as oxyfuel or saws.
- Easy to set up and operate. Powermax SYNC systems automatically adjust the system for the consumable installed, eliminating costly errors.
- Piercing capability makes starting interior cuts easy.
- High cut quality reduces or eliminates secondary operations, such as grinding.
- Drag-cutting technology makes it easy to follow a line or template.
- Gouging process efficiently removes existing welds with reduced noise and smoke over conventional methods.
- A wide variety of torch designs and specialty consumables make it easy to get any cutting or gouging job done.
- System portability offers ease of use at various locations.
- Controlled arc and high cutting speeds reduce heat-affected zone and warping.
- Cut a variety of ferrous and non-ferrous metals including mild steel, stainless and aluminum – painted or rusted.

Hypertherm, SYNC, and Powermax are trademarks of Hypertherm, Inc. and may be registered in the United States and/or other countries. All other trademarks are the properties of their respective owners.

© 3/2021 Hypertherm, Inc. Revision 6
890440

