

Laser ProNest process support

Introduction

Users of ProNest advanced nesting software gain an advantage when able to program for more than one cutting process. Using a single software solution to program for plasma, laser, waterjet, and oxyfuel machines can result in:

- Reduced cost of software ownership (upgrade charges, maintenance fees, etc).
- Reduced employee (programmer) training requirements.
- Reduced business risk by making it easy for any employee to program any cutting machine using a single software product.
- Increased flexibility allowing NC output for alternate cutting processes during a machine failure.

ProNest assists companies that cut parts by providing the above benefits and delivering programming capability for virtually all plasma, laser, waterjet, oxyfuel and punch combination machines, regardless of machine brand or model.



ProNest laser process support overview

ProNest offers complete support for both CO₂ and fiber laser cutting processes.

Below is an overview of the laser-specific capabilities you'll find in ProNest. Note that some machine manufacturers have their own naming convention for a number of the capabilities listed below. Please contact us with any questions you have concerning machine support not listed.

- Collision avoidance – including full and partial head raise control
- Common line cutting (with array)
- Fiber laser and plasma combo – numerous parameter configurations
- Grain constraint
- Height sensing cutting – capacitive/freeze
- Interior cut-up
- Part Program Support – NC code integration of advanced commands for automatic job loading on the CNC
 - Wattage
 - Gas type and pressure
 - Pierce height
 - Pierce time
 - Cut height
- Process parameters
 - Automatic and interactive separations for part, plate, and pierce spacing
 - Material type, thickness, grade and class-based process parameters such as:
- Advanced kerf commands
- Corner radiusing
- Cut mode – cw/etching/pulse/vaporizing
- Cutting assist gas – type, pressure and cut flow
- Feed rates – machine/material dependent interior and exterior techniques
- Focal length
- Micro-joints
- Piercing (no pierce/pre-pierce/pulse/rapid/“double pump” etc.)
- Power setting control – step (fast, medium, slow)/dynamic power
- Ramping – lead-in with/out power, end cut/initial geometry/intersection corner

ProNest laser process support overview, continued

- Rapid move commands – numerous parameter configurations
- User defined variables – customization tech tables/override on the fly/direct commands
 - Material type and thickness-based lead parameters including various lead styles, angles, extensions and over-travels
- Safety cuts
- Skeleton cut-up
- Repositioning machine support for punch combination machines



ProNest, and Hypertherm Associates are trademarks of Hypertherm Inc. and may be registered in the United States and/or other countries. All other trademarks are the property of their respective owners.

Please visit www.hypertherm.com/patents for more details about Hypertherm Associates patent numbers and types.

© 2/2023 Hypertherm Inc. Revision 4
896050



As 100% Associate owners, we are all focused on delivering a superior customer experience. www.hyperthermassociates.com/ownership

Environmental stewardship is one of Hypertherm Associates' core values. www.hyperthermassociates.com/environment

100% Associate-owned

