

Powermax125 – Plasma Cutting System

Electromagnetic Field (EMF) Measurements

Introduction

Electric and magnetic fields are often referred to as “electromagnetic fields,” or EMF. The EMF generated by Hypertherm plasma arc cutting equipment is not significant when operated and installed according to Hypertherm’s instructions to minimize EMF.

How Do I Minimize EMF Exposure?

Failure to follow these instructions will increase EMF:

- Cut with the lowest current setting necessary for the application and quality of the cut.
- Never coil a torch cable or work lead around your body.
- Do not place your body between the torch cable and work lead.
- Route cables together on the same side of your body.
- Route the torch cable and work lead close together. If possible, secure them together with tape or cable ties.
- Connect the work cable to the workpiece as close to the cutting zone as practical.
- Keep the cutting power source and cables as far away from you as practical.

European EMF Directive (2013/35/EU amending 2008/46/EC & 2004/40/EC)

The European Commission published Directive 2013/35/EU on the minimum health and safety requirements regarding the exposure of workers to the risks arising from physical agents such as electromagnetic fields (EMF). The new feature of the EMF Directive effective July 2016 is the requirement that employers must assess the risk separately for each workplace. Risk assessment of electromagnetic fields in the workplace (including measurements or calculations, if necessary) should be carried out. Where applicable, special attention shall be paid to workers at particular risks (i.e. pregnant, living with implanted medical devices, etc.). The employer shall consider updating the risk assessment and the prevention measures if workers report transient symptoms in relation to their sensory/neural system. Health surveillance shall be carried out by the employer and the findings preserved.

Hypertherm EMF measurements

Measurements were taken per EN50444 figure A.1 and IEC 62822-2 figures 7, 11, and 15 as shown below.

The highest field strength is usually to be expected at close distance to the welding cable, torch or electrode holder. For measurement the point of investigation (POI) for maximum exposure evaluation due to cables should be at the centre of a quarter circle with a radius $r = 20$ cm, see Figure A.1.



Figure A.1 – Probe position for measurement on welding cables




Figure 7 – Field measurement at head position




Figure 11 – Field measurement at trunk position





Figure 15 – Field measurement at limb positions, hand and thigh

Powermax125 – Plasma Cutting System

Electromagnetic Field (EMF) Measurements

Power Source Model	Meter used	Range	Ambient (μT)	IEC 62822-2 Hand/Thigh d=3 cm (μT)	IEC 62822-2 Head/Trunk d=10 cm (μT)	EN50444 r=20 cm (μT)	Date Measurement Taken
Powermax125	Narda ELT-400	1Hz – 400KHz	5.47	28.3	16.7	16.5	1-Dec-16
	Narda ELT-400	30Hz - 400KHz	2.04	21.2	13.2	11.2	1-Dec-16
	Omega HHG-23	DC	0	540	420	400	1-Dec-16

Notes:

1. The above data was measured for reference only in Hypertherm’s R&D lab environment over multiple days with other equipment running in the lab.
2. The positioning of the measurement equipment used results in variation of measurements.
3. The AC component was measured with the Narda ELT-400 and the DC component was measured with the Omega HHG-23.
4. Non-thermal effects due to electric fields per IEC 62822-1:2016 4.3 complies because the welding equipment is designed in accordance with IEC 60974-1.
5. There are no contact currents per IEC 62822-1:2016 4.4
6. Non-thermal effects of output current ripple per IEC 62822-1:2016 4.5 are exempt because the ripple current for the above products is less the 100A peak to peak.
7. Thermal effects per IEC 62822-1:2016 4.6 are exempt because the ripple current for the above products is less then 300A peak to peak.

Revision	Date	Section	History Change
1	1-December-2016	-	Initial Release