

Powermax85 SYNC

Recommended cut capacity of 25 mm (1")

Severance capacity of 38 mm (1-1/2")

Professional grade



Part of the Powermax[®] family, the Powermax85 SYNC features advanced torch communication for automated setup and patented single-piece cartridges for hand cutting, mechanized or robotic cutting, or gouging.

Key business benefits

Simplify operations and boost productivity

Single-piece cartridge simplifies operations and dramatically reduces training time

Minimize operating costs

Up to 5x longer consumable life compared to competitors decreases operating costs

Reduce secondary operations

Improved cut quality over consumable life delivers better part consistency to reduce secondary operations

Powermax85 SYNC cut and gouge capacities

Cut capacity	Thickness	Cut speed
Recommended	25 mm (1")	500 mm/min (20 ipm)
	32 mm (1-1/4")	250 mm/min (10 ipm)
Severance (hand cutting)	38 mm (1-1/2")	125 mm/min (5 ipm)
Pierce*	20 mm (3/4")	
*Pierce rating for handheld use or with automatic torch height control		
Gouge capacity	Metal removal rate	Groove profile
Typical gouge	8.2 kg (18.2 lbs) per hour	3.2 mm (.12") D x 6.8 mm (.26") W

Torch output**	12.2 kW
	85 A x 143 V ÷ 1000 W = 12.2 kW

**Higher output voltage at the torch plus efficiently designed consumables result in a faster, cleaner cut.

Powermax85 SYNC. Easy to use. Versatile. Reliable.

For metal workers who want the most versatile system available to gouge and cut, Powermax85 SYNC delivers the best return on investment. It features a patented single-piece cartridge, greater cutting power than higher-amperage competitors, an automated system process set-up, and SmartSYNC[®] torches that provide trackable utilization data.

“We’re very impressed with the machine’s cut quality and love the cartridges. The cartridge life span far exceeds our older machine’s consumables, and the cartridge takes seconds to replace.”

Salt Creek Fab, United States

**THE BEST
INVESTMENT
IS IN YOUR
POWER**

Our customers' preferred cutting tool for industries including:

- Job shops and general fabrication
- Truck and trailer fabrication
- Tank and vessel fabrication
- Railyard maintenance and railcar fabrication
- Demolition and metal salvage
- Agricultural/equipment maintenance

Highlighted product features:

Easy to use

- SmartSYNC® torches with the cartridge automatically set the correct amperage and operating mode, eliminating setup errors
- Easy to identify single-piece cartridges are color-coded by process to eliminate parts mix-up and simplify consumable inventory management
- End-of-life detection lets the operator know when it's time to change the cartridge
- Simplified operation minimizes downtime, troubleshooting, waste, and training time

Versatile

- Tackle a wide range of jobs with easily interchangeable torch styles and application-specific cartridges for various types of cutting and gouging
- Time-saving torch controls allow the operator to adjust the amperage on the fly and change cartridges and applications without returning to the power supply
- Access cartridge data for performance tracking and analyzing usage patterns

Industry-leading reliability

- Powermax plasma cutters are known to last decades in the field, minimizing maintenance and downtime
- Power supplies and torches are engineered for rugged industrial environments
- Each Powermax component is tested to perform reliably in demanding conditions

Specifications

CE – for use in Europe, Australia & New Zealand - RCM, Serbia, UK – UKCA, Ukraine, and other countries where accepted.

CCC – for use in China

CSA – for use in the Americas and Asia, except China

CE	CCC	CSA	
Input voltages (± 10%)			
		↳	200-480 V, 1-PH, 50/60 Hz
		↳	200-600 V, 3-PH, 50/60 Hz
↳	↳		400 V, 3-PH, 50-60 Hz
Input current @ 12.2 kW			
		↳	200/208/240/480, 1-PH 70/68/58/29 A
		↳	200/208/240/480/600 V, 3-PH 42/40/35/18/17 A
↳	↳		380/400 V, 3-PH 20.5/19.5 A
Output current			25-85 A
Rated output voltage			143 VDC
Duty cycle @ 40° C (104° F)			
		↳	60% @ 85 A, 230-600 V, 3-PH
		↳	60% @ 85 A, 480 V, 1-PH
		↳	50% @ 85 A 240 V, 1-PH
		↳	50% @ 85 A, 200-208 V, 3-PH
		↳	40% @ 85 A, 200-208 V, 1-PH
		↳	100% @ 66 A, 230-600 V, 1/3-PH
↳	↳		60% @ 85 A, 380-400 V, 3-PH
↳	↳		100% @ 66 A, 380-400 V, 3-PH
Open circuit voltage (OCV)			
		↳	305 VDC
↳	↳		270 VDC
Dimensions with handles			483 mm D; 233 mm W; 430 mm H (19" D; 9.2" W; 17" H)
Weight with 7.6 m (25') torch			
		↳	32 kg (67 lbs.)
↳	↳		23.5 kg (52 lbs.)
Gas supply			Clean, dry, oil-free air or nitrogen
Optimum inlet gas pressure			7.6-8.3 bar (110-120 psi)
Minimum inlet gas pressure			5.2 bar (75 psi)
Recommended gas inlet flow rate/pressure			Cutting: 210 l/min @ 5.9 bar (450 scfh, 7.5 scfm @ 85 psi) Gouging: 210 l/min @ 4.8 bar (450 scfh, 7.5 scfm @ 70 psi)
Input power cable length			3 m (10')
Power supply type			Inverter – IGBT
Engine drive requirement			20 kW or 25 kVa for full 85 A output
Electrical efficiency			91.9%
Recyclability			100%
Warranty			Power supply: 3-year, Torch: 1-year

Ordering information

Below are the standard system configurations, which include a power supply, torch and work cable.

<p>CE – for use in Europe, Australia & New Zealand - RCM, Serbia, UK – UKCA, Ukraine, and other countries where accepted.</p> <p>CCC – for use in China</p> <p>CSA – for use in the Americas and Asia, except China</p>			75° hand torch			75° and 15° hand torch			180° full-length machine torch			180° full-length machine torch and 75° hand torch		
CE	CCC	CSA	Torch lead length			7.6 m (25')	15.2 m (50')	7.6 m (25')	7.6 m (25')	10.7 m (35')	15.2 m (50')	10.7 m/7.6 m (35'/25')		
			✓ = With remote pendant						✓		✓	✓		

Powermax85 SYNC® power supplies				Handheld			Mechanized							
↳	↳		Standard power supply	087196	087197	087200								
		↳	Standard power supply	087183	087184	087187								
↳	↳		Power supply with CPC port and voltage divider	087198	087199		087201	087202			087203	087204		
		↳	Power supply with CPC port and voltage divider	087185	087186		087207	087189		087208	087190			
↳	↳		Power supply with CPC port, voltage divider, and serial port					087205	087220		087206			
		↳	Power supply with CPC port, voltage divider, and serial port				087192		087218 *		087219 *			

* with ring terminated work lead

Custom configurations

Select power supply, torch, work cable, cartridge, and other components

Power supply options

<p>CE – for use in Europe, Australia & New Zealand - RCM, Serbia, UK – UKCA, Ukraine, and other countries where accepted.</p> <p>CCC – for use in China</p> <p>CSA – for use in the Americas and Asia, except China</p>			Standard			With CPC port and voltage divider			With CPC port, voltage divider and serial port			
CE	CCC	CSA										
↳	↳		Powermax85 SYNC 380–400 V	087210			087211			087212		
		↳	Powermax85 SYNC 200–600 V	087213			087214			087215		

Work leads

	Hand clamp	C-clamp	Ring terminal
7.6 m (25')	223035	223203	223209
15.2 m (50')	223034	223204	223210
22.8 m (75')	223033	223205	223211

Cable options

Control cables						
Cable length	Remote pendant	CNC, spade connector, divided voltage	CNC, spade connector, no divided voltage	CNC, D-sub connector, divided voltage	RS-485 Serial comm, unterminated	RS-485 Serial comm, D-sub
7.6 m (25')	128650	228350	023206	223048	223236	223239
15.2 m (50')	128651	228351	023279	123896	223237	223240
22.8 m (75')	128652					

Torch options

	Hand torches		Long torches				Machine torches	Robotic/Mini		
	75°	15°	0.6 m (2'), 45°	0.6 m (2'), 90°	1.2 m (4'), 45°	1.2 m (4'), 90°	180°	180°	90°	45°
4.5 m (15')								059733		
7.6 m (25')	059726	059723			528114		059719	059734	059731	059729
10.7 m (35')							059720			
15.2 m (50')	059727	059724	528116	528117	528118	528119	059721	059735	059732	059730
22.8 m (75')	059728	059725					059722		059767	059766
30 m (100')	059770									

Powermax cartridge options

	Drag cutting	Mechanized/standoff cutting	Max removal gouging	Max control gouging	Ohmic ring kit
45 A	428927	428925	428932	428933	428895*
65 A	428931	428930			
85 A	428935	428934			

	FlushCut™	FineCut®		HyAccess™		
		Handheld	Mechanized	Drag cutting	Gouging	Mechanized
30-45 A		428928	428926			
65 A	428952			428984	428987	528079
85 A	428953					



Cartridge reader

The cartridge reader works with the Powermax SYNC® cartridge reader app to provide a simple process for reviewing data stored in Powermax cartridges. Part number 528083

*Kit includes three 420580 ohmic ring clips.

Torches and cartridges



Learn more at www.hypertherm.com/powermax85sync

Unless otherwise noted in the collateral, all trademarks are property of Hypertherm, Inc. and may be registered in the United States and/or other countries.

Please visit www.hypertherm.com/patents for more details about Hypertherm Associates patent numbers and types.

© 4/2024 Hypertherm, Inc. Revision 0

898590

As 100% Associate owners, we are all focused on delivering a superior customer experience. www.hyperthermassociates.com/ownership

Environmental stewardship is one of Hypertherm Associates' core values. www.hyperthermassociates.com/environment

100% Associate-owned

