

Powermax125

Recommended cut capacity of 38 mm (1-1/2")

Severance capacity of 57 mm (2-1/4")

Professional grade



Part of the Powermax® family, the Powermax125 features a 100% duty cycle for the most demanding mechanized or robotic cutting, or gouging.

Key business benefits

Boost productivity

Finish jobs faster with cut speeds five times greater than oxyfuel on 12 mm (1/2") mild steel

Minimize operating costs

Consumable life up to four times longer than other systems in this amperage range

Reduce secondary operations

Superior cut and gouge quality lets you spend less time grinding and preparing edges

Maximum power and performance.

The Powermax125® cuts thick metals fast and makes short work of your toughest cutting and gouging jobs. It offers a 100% duty cycle for maximum operation time, making it the preferred system for many mechanized or robotic cutting jobs. Smart Sense™ technology automatically adjusts the gas pressure so you can focus on the job and not the setup.

Cut and gouge capacities

Cut capacity	Thickness	Cut speed
Recommended	38 mm (1-1/2")	457 mm/min (18 ipm)
	44 mm (1-3/4")	250 mm/min (10 ipm)
Severance (hand cutting)	57 mm (2-1/4")	125 mm/min (5 ipm)
Pierce*	25 mm (1")	

*Pierce rating for handheld use or with automatic torch height control

Gouge capacity	Metal removal rate	Groove profile
Typical gouge	12.52 kg/hr (27.6 lbs/hr)	4.3-7.9 mm D x 6.1-9.9 mm W (0.17-0.31" D x 0.24-0.39" W)

Torch output**	21.9 kW
	125 A x 175 V ÷ 1000 W = 21.9 kW

**Higher output voltage at the torch plus efficiently designed consumables result in a faster, cleaner cut.

Make short work of your toughest cutting and gouging jobs with the Powermax125.

THE BEST INVESTMENT IS IN YOUR POWER

Our customers' preferred cutting tool for industries including:

- Shipbuilding/ship repair
- Truck and trailer fabrication
- Tank and vessel manufacturing
- Railyard maintenance and railcar fabrication
- Demolition and metal salvage
- Agricultural/equipment maintenance

Highlighted product features:

Easy to use

- No need to change the air pressure – Smart Sense™ technology ensures it's correctly set
- Superior cut and gouge quality lets you spend less time on grinding and edge preparation
- Electrode end-of-life detection protects the torch and workpiece from damage by automatically stopping power when the electrode is overused
- 100% duty cycle maximizes your operating time

Low operating costs

- Duramax® Hyamp™ torch styles provide versatility for, portable automation, X-Y table cutting, and robotic cutting
- Six types of consumables for drag cutting, fine feature cutting, flush cutting, mechanized cutting, plus maximum control and removal gouging

Industry-leading reliability

- Powermax plasma cutters are known to last decades in the field, minimizing maintenance and downtime
- Power supplies and torches are engineered for rugged industrial environments
- Each Powermax component is tested to perform reliably in demanding conditions
- SpringStart™ technology ensures consistent starting and a more reliable torch

Specifications – CCC

Input voltages (± 10%)	380 V, 3-PH, 50/60 Hz
Input current @ 12.2 kW	380 V, 3-PH, 38 A 400 V, 3-PH, 36 A
Output current	30-125 A
Rated output voltage	175 VDC
Duty cycle @ 40° C (104° F)	100% @ 125 A, 380/400 V, 3-PH
Open circuit voltage (OCV)	290 VDC
Weight with 7.6 m (25') torch	380 V 45.2 kg 400 V 48.9 kg

CCC – for use in China.

Dimensions with handles	483 mm D; 233 mm W; 430 mm H (19" D; 9.2" W; 17" H)
Gas supply	Clean, dry, oil-free air or nitrogen
Recommended gas inlet flow rate/pressure	Cutting: 260 l/min (550 scfh) @ 5.9 bar (85 psi) Gouging: 212 l/min (450 scfh) @ 4.1 bar (60 psi)
Input power cable length	3 m (10')
Power supply type	Inverter – IGBT
Engine drive requirement	40 kW or 50 kVA for full 125 A output
Electrical efficiency	91%–92%
Recyclability	100%
Warranty	Power supply: 6-year, Torch: 1-year

Ordering information – CCC

Below are the standard systems configurations, which include a power supply, torch or torches, work cable, and consumable kit.

CCC – for use in China.	180° full-length machine torch		180° full-length machine torch and 75° hand torch		
	7.6 m (25')	7.6 m (25') with I/O cables	15.2 m (50')	15.2 m (50') with I/O cables	15.2m/7.6 m (50'/25')
Torch lead length					
✓ = With remote pendant	✓		✓		✓
Powermax125® power supplies	Mechanized				
380 V CCC power supply with CPC port and voltage divider	059558	059583		059584	
380 V CCC power supply with CPC port, voltage divider, and serial port		059560		059561	

Custom configurations – CE

Select power supply, torch, work cable, and other components.

	With CPC port and voltage divider	With CPC port, voltage divider and serial port
Powermax125® 380 V CCC	059490	059491

Work leads

	Hand clamp	C-clamp	Rign terminal
7.6 m (25')	223292	223298	223295
15.2 m (50')	223293	223299	223296
22.8 m (75')	223294	223300	223297
45.7 m (150')	223737		223744

Cable options

Cable length	Remote pendant	Control cables				
		CNC, spade connector, divided voltage	CNC, spade connector, no divided voltage	CNC, D-sub connector, divided voltage	RS-485 Serial comm, unterminated	RS-485 Serial comm, D-sub
7.6 m (25')	128650	228350	023206	223048	223236	223239
15.2 m (50')	128651	228351	023279	123896	223237	223240
22.8 m (75')	128652					

Torch options

Cable length	Machine torches		Robotic torches		
	180°	Mini 180°	45°	90°	180°
4.5 m (15')	059519	059514			
7.6 m (25')	059520	059515	059564	059565	059566
10.7 m (35')	059521	059516			
15.2 m (50')	059522	059517	059670	059671	059672
22.8 m (75')	059523				
45.7 m (150)*		059666			

*45.7 m (150) torch leads are compatible only with Powermax125 systems with a serial number of 125-007944 or higher.

Torch consumable parts

Nozzles and electrodes are available in various quantities. Contact your distributor for more information.

Consumable type	Torch type	Amperage	Nozzle	Shield/Deflector	Retaining cap	Swirl ring	Electrode
Mechanized	Machine	45	420158	420168	220977 or 420156 ¹	220997	220971
		65	420169	420168			
		125/105	220975	220976			
	Machine	45	420151	420152	220977 or 420156 ¹	220997	220971
Max removal gouging	Machine	30-125	420001	420112	220977	220997	220971
Max control gouging	Machine	30-125	420001	420509	220977	220997	220971

¹ Ohmic retaining cap

Torches and consumables



Learn more at www.hypertherm.com/Powermax125

Unless otherwise noted in the collateral, all trademarks are property of Hypertherm, Inc. and may be registered in the United States and/or other countries.

Please visit www.hypertherm.com/patents for more details about Hypertherm Associates patent numbers and types.

© 11/2025 Hypertherm, Inc. Revision 4

860870

As 100% Associate owners, we are all focused on delivering a superior customer experience. www.hyperthermassociates.com/ownership

Environmental stewardship is one of Hypertherm Associates' core values. www.hyperthermassociates.com/environment

100% Associate-owned

